

Parking stop

Purpose:

- Optimises the use of parking and garage space. Enables safe parking.

Place of production:

Geyer & Hosaja Sp. z o. o.
Partynia 12
39-310 Radomyśl Wielki

Material:

Vulcanised rubber
3M reflective tape
Metal reinforcements for mounting

Dimensions:

width 750 mm
length 120 mm
height 100 mm

Weight: 6,0 kg

Colour:

black, red (other colours on request)
white 3M reflective tape

**Technical parameters:**

Parameters	Value	Unit	Standard / Method
Tensile strength	≥ 4,0	MPa	PN-ISO 37
Hardness	≥ 60	°ShA	PN-EN ISO 868:2005
Water absorption	≤ 2	%	PN-EN ISO 62
Tolerance - length, width	± 2	%	of nominal
Tolerance - height	± 2	%	of nominal
Tolerance- weight	± 2	%	of nominal

Packing:

Packed in a cardboard box on a Euro pallet, 100 pieces.

Description on the pallet with the name of product, quantity, batch number and packing date.

On customer's request other way of packaging is possible.

Identification:

Product- on the underside of the product information about the date of production.

Pallet- product name, quantity, pallet identification number, packing date, quality control stamp.

Storage:

The products should be stored on pallets in protective film and protected from external weather conditions.

The products may be stored for a longer period of time only in closed, ventilated rooms without humidity, after removing the protective film. Storage temperature: max 40 °C

Health, safety and fire conditions:

Conditions for storage and use of the product- must meet all requirements for storage and use of rubber materials.