

Point separator

Purpose:

- temporary and permanent separation of lanes,
- horizontal markings
- the applied openings enable the installation of vertical markings and additional reflectors

Place of production:

Geyer & Hosaja Sp. z o. o.
Ul. Gorliczyńska 157
37-200 Przeworsk

Material:

SBR rubber granulate
PUR resin
White/ yellow 3M reflective tape

Dimensions:

length 1000 mm
width 240 mm
height 80 mm
weight 11 kg

holes \varnothing 45
 40
 60

Colour:

Black/ yellow
White/ yellow 3M reflective tape

**Technical parameters:**

Parameters	Value	Unit	Standard / Method
Tensile strength	$\geq 1,0$	MPa	PN-ISO 37
Hardness	≥ 55	°ShA	PN-EN ISO 868:2005
Water absorption	≤ 2	%	PN EN ISO 62:2000
Tolerance - length, width	± 2	%	of nominal
Tolerance - height	± 2	%	of nominal
Tolerance- weight	± 2	%	of nominal

Packing:

Packed on a Euro pallet with 60 pieces.

Description on the pallet with the name of product, quantity, batch number and packing date.

Other packaging is possible on request

Identification:

Product- on the underside of the product information about the date of production.

Pallet- product name, quantity, pallet identification number, packing date, quality control stamp.

Storage:

The products should be stored on pallets in protective film and protected from external weather conditions.

The products may be stored for a longer period of time only in closed, ventilated rooms without humidity, after removing the protective film. Storage temperature: max 40 °C

Health, safety and fire conditions:

Conditions for storage and use of the product- must meet all requirements for storage and use of rubber materials.