

## Flexible road bollards U-24

**Purpose:**

- temporary and permanent lane separation, horizontal road marking

- the intensive-coloured rubber used guarantees excellent visibility as well as flexibility and resistance to impact

**Place of production:**

Geyer & Hosaja Sp. z o. o.  
Partynia 12  
39-310 Radomyśl Wielki

**Material:**

Vulcanised rubber  
Reflective elements (glass beads) applied to both sides  
of the sign to increase visibility

**Colour:**

Base- yellow  
Tongue- red

**Dimensions:**

base (L x W)                      158 x 148 mm  
height                              285 mm

**Weight:**

1 kg

**Technical parameters:**

Parameters	Value	Unit	Standard / Method
Tensile strength	≥ 6,0	MPa	PN-ISO 37
Hardness (base - yellow element)	85 (±5)	°ShA	PN-EN ISO 868:2005
Hardness (tongue - red element)	70 (±5)	°ShA	PN-EN ISO 868:2005
Tolerance - length, width	± 2	%	of nominal
Tolerance - height	± 2	%	of nominal
Tolerance- weight	± 2	%	of nominal

**Packing:**

The method of packaging is determined individually, depending on the order.

Description with product name, quantity, batch number and packing date on the pallet.

**Identification:**

Pallet/ cardboard box- product name, quantity, pallet identification number, packing date, quality control stamp.

**Storage:**

The products should be stored on pallets in protective film and protected from external weather conditions.

The products may be stored for a longer period of time only in closed, ventilated rooms without humidity, after removing the protective film. Storage temperature: max 40 °C

**Health, safety and fire conditions:**

Conditions for storage and use of the product- must meet all requirements for storage and use of rubber materials.